

Brad Nailer SK 350-224C

12000467



**Fastener type**

BeA Countersunk nails SK 300  
· Length: 18 - 50 mm

**Scope of operation**

Dry and interior extension, Joinery, Roofing and facade, Window and door construction, Wooden constructions

**Scope of delivery**

Sparepart list, User manual

More details:




**Technical data**

|  |                              |
|--|------------------------------|
| EAN  | 4045759004387                |
| Type of fastener   | BeA Countersunk nails SK 300 |
| Fastener length min                                      | 18 mm                        |
| Fastener length max                                      | 50 mm                        |
| Tool magazin slope                                       | 0 °                          |
| Magazine capacity max                                    | 104 pc                       |
| Weight   | 1,24 kg                      |
| Driving system   | Compressed air               |
| Activation method  | Contact activation           |
| Operating pressure min                                   | 5 bar                        |
| Operating pressure max                                   | 8 bar                        |
| Air consumption per drive operation                      | 0,9 l (6 bar)                |
| Tool length  | 248 mm                       |
| Tool width   | 59 mm                        |
| Tool height  | 233 mm                       |
| BG eligible for funding                                  | No                           |
| Declaration of conformity                                | CE, EAC, UKCA                |
| Noise characteristic L pA, 1s according to EN 12549      | 88,9 dB(A)                   |
| Noise characteristic L WA. 1s, d according to EN 12549   | 95,4 dB(A)                   |
| Noise characteristic K pA and K WA according to EN 12549 | 2,5 dB(A)                    |
| Vibration value ahd according to ISO 8662                | 1,5 m/s <sup>2</sup>         |
| Vibration value Ka according to ISO 8662                 | 0,7 m/s <sup>2</sup>         |

**Technical data**

|                        |         |
|------------------------|---------|
| Weight incl. packaging | 1,92 kg |
|------------------------|---------|

## Related fastener



## BeA Countersunk nails SK 300

- Diameter: 1,2 mm
- Length: 19 - 50 mm

| Item No. | Diameter x Length | Nail shank   | Material   |
|----------|-------------------|--------------|--|
| 10300268 | 1,2 mm x 19 mm    | Smooth shank | Steel, galvanized                                |
| 10300337 | 1,2 mm x 30 mm    | Smooth shank | Stainless Steel, (AISI 316, EN grade 1.4401, A4) |
| 10300338 | 1,2 mm x 35 mm    | Smooth shank | Stainless Steel, (AISI 316, EN grade 1.4401, A4) |
| 10300644 | 1,2 mm x 20 mm    | Smooth shank | Steel, galvanized                                |
| 10300645 | 1,2 mm x 25 mm    | Smooth shank | Steel, galvanized                                |
| 10300646 | 1,2 mm x 30 mm    | Smooth shank | Steel, galvanized                                |
| 10300648 | 1,2 mm x 35 mm    | Smooth shank | Steel, galvanized                                |
| 10300649 | 1,2 mm x 38 mm    | Smooth shank | Steel, galvanized                                |
| 10300650 | 1,2 mm x 40 mm    | Smooth shank | Steel, galvanized                                |
| 10300651 | 1,2 mm x 45 mm    | Smooth shank | Steel, galvanized                                |
| 10300652 | 1,2 mm x 50 mm    | Smooth shank | Steel, galvanized                                |
| 10300717 | 1,2 mm x 32 mm    | Smooth shank | Steel, galvanized                                |

**Other variations and sizes on request**